

View Online at <https://aerobasegroup.com/nsn/5915-01-067-8364>

Overall Height:

1.030 inches

Body Length:

2.000 inches

Body Width:

1.600 inches

Body Height:

0.780 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.100 inches

Operating Temperature Range:

-46.0/+87.0 degrees celsius

End Application:

Whidbey island class lsd; nimitz class cvn; airborne mobile dir air spt ctl (21d), (02m jul 83) (an/uyq-3a); radio set (a185) (an/grc-193); wasp class lhd; radio set (an/mrc-138); forrestal class cv; supply class aoe; osprey class mhc

Reference Frequency Per Function:

3.0 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Inclosure Type:

Encased

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

1.00 kilohertz blank and 2.00 kilohertz blank and 4.00 kilohertz blank and 6.00 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

2.00 kilohertz blank and 4.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 5.0 blank and 5.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

2.0 kilohertz blank and 4.0 kilohertz blank

Body Surface Treatment:

Tin

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0