## NSN 5915-01-068-6409

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-068-6409

## **Overall Height:**

3.843 inches

#### **Body Length:**

1.781 inches

## **Body Width:**

1.781 inches

#### **Body Height:**

#### 3.531 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

#### **Operating Tempurature Range:**

-0.0/+75.0 degrees celsius

#### **Reference Frequency Per Function:**

214.0 kilohertz blank

#### Source Impedance Rating Per Function:

10.0 kilohms blank

#### Load Impedance Per Function:

10.0 kilohms blank

## Mounting Facility Screw Thread Series Designator:

Unc

#### Inclosure Type:

Encased

#### Mounting Facility Type And Quantity:

4 threaded hole

#### Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

#### Functional Terminal Type And Quantity:

1 pin output 2nd function

#### **Specified Frequencies Of Discrimination Per Function:**

202.00 kilohertz blank and 213.00 kilohertz blank and 215.00 kilohertz blank and 225.00 kilohertz blank

#### **Thread Size:**

0.138 inches

#### **Body Material:**

Metal

#### Frequency Band Width Per Function:

213.00 kilohertz blank and 215.00 kilohertz blank

## Discrimination At Specificationified Frequencies Per Function In Decibels:

 $40.0\,$  blank and  $4.5\,$  blank and  $4.5\,$  blank and  $40.0\,$  blank

## Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

# NSN 5915-01-068-6409

Band Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0