

View Online at <https://aerobasegroup.com/nsn/5915-01-069-0328>

Body Length:

2.812 inches

Body Width:

1.000 inches

Body Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+91.0 degrees celsius

Reference Frequency Per Function:

18.0 megahertz blank

Source Impedance Rating Per Function:

5.0 kilohms blank

Load Impedance Per Function:

2.5 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encapsulated or hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 wire lead ground 3rd function

Specified Frequencies Of Discrimination Per Function:

17.955 megahertz blank and 17.975 megahertz blank and 18.025 megahertz blank and 18.045 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

17.975 megahertz blank and 18.025 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Maximum Dielectric Withstanding Dc Voltage:

200.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0