NSN 5915-01-073-0231

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-073-0231

1.150 inches Body Length: 2.340 inches Body Width: 1.032 inches Body Height: 0.800 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input: 50.0 ohms blank
2.340 inches Body Width: 1.032 inches Body Height: 0.800 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
Body Width: 1.032 inches Body Height: 0.800 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
1.032 inches Body Height: 0.800 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
Body Height: 0.800 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
0.800 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
1.936 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
0.562 inches End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
End Application: An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
An/grr23/24 Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
Reference Frequency Per Function: 20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
20.6 megahertz blank Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
Input Impedance Per Function W/load: 50.0 ohms blank Output Impedance Per Function W/source Across Input:
50.0 ohms blank Output Impedance Per Function W/source Across Input:
Output Impedance Per Function W/source Across Input:
50.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
6.0 blank
Functional Terminal Type And Quantity:
1 connector, plug output 2nd function
Specified Frequencies Of Discrimination Per Function:
7.00 megahertz blank and 60.00 megahertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:
20.30 megahertz blank and 20.90 megahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
100.0 blank
Special Features:
T.O. 31r2-2grr-114; n/h/a radio receiver
Style Designator:
Rectangular terminal/terminals on one surface

NSN 5915-01-073-0231

Band Pass Filter - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0