

View Online at <https://aerobasegroup.com/nsn/5915-01-074-1762>

Overall Height:

1.422 inches

Body Length:

2.370 inches

Body Width:

1.015 inches

Body Height:

1.047 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.800 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

End Application:

0spruance class dd (963), kidd class ddg, virginia class cgn (41), ticondeoroga class cg (47), forrestal class cv, nimitz class cvn, oliver perry class ffg, arleigh burke class ddg. Airborne mobile dir air spt ctl (2id) (02mjul83) an/uyq-3a.

Reference Frequency Per Function:

10.7 megahertz blank

Source Impedance Rating Per Function:

4.0 kilohms blank

Load Impedance Per Function:

4.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

10.675 megahertz blank and 10.691 megahertz blank and 10.709 megahertz blank and 10.725 megahertz blank

Thread Size:

0.125 inches

Frequency Band Width Per Function:

10.691 megahertz blank and 10.709 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

80.0 blank and 1.0 blank and 1.0 blank and 80.0 blank

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0