

View Online at <https://aerobasegroup.com/nsn/5915-01-075-0006>

Overall Height:

0.920 inches

Body Length:

2.380 inches

Body Width:

0.980 inches

Body Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Vibration Resistance Range In Hertz:

+14.0/+200.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.588 inches

Reference Frequency Per Function:

70.0 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

2.1 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

13.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

67.00 megahertz blank and 69.90 megahertz blank and 70.10 megahertz blank and 73.00 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

69.90 megahertz blank and 70.10 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 1.0 blank and 1.0 blank and 30.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

69.9 megahertz blank and 70.1 megahertz blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0