

View Online at <https://aerobasegroup.com/nsn/5915-01-075-0006>

**Overall Height:**

0.920 inches

**Body Length:**

2.380 inches

**Body Width:**

0.980 inches

**Body Height:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.000 inches

**Vibration Resistance Range In Hertz:**

+14.0/+200.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.588 inches

**Reference Frequency Per Function:**

70.0 megahertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

2.1 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

13.0 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

67.00 megahertz blank and 69.90 megahertz blank and 70.10 megahertz blank and 73.00 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

69.90 megahertz blank and 70.10 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

30.0 blank and 1.0 blank and 1.0 blank and 30.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

69.9 megahertz blank and 70.1 megahertz blank

**Body Surface Treatment:**

Tin

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0