NSN 5915-01-076-0402

Band Pass Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5915-01-076-0402 |
|--|
| Overall Height: |
| 1.110 inches |
| Body Length: |
| 3.000 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 1.495 inches and 1.505 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.370 inches and 0.380 inches |
| Reference Frequency Per Function: |
| 10.5 megahertz blank |
| Input Impedance Per Function W/load: |
| 50.0 ohms blank |
| Output Impedance Per Function W/source Across Input: |
| 50.0 ohms blank |
| Voltage Standing Wave Ratio Per Function: |
| 1.8 blank |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 2 threaded stud |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 3.25 blank |
| Functional Terminal Type And Quantity: |
| 2 pin ground 1st function |
| Specified Frequencies Of Discrimination Per Function: |
| 9.80 megahertz blank and 10.00 megahertz blank and 11.00 megahertz blank and 11.20 megahertz blank |
| Thread Size: |
| 0.112 inches |
| Frequency Band Width Per Function: |
| 10.00 megahertz blank and 11.00 megahertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 6.0 blank and 1.5 blank and 6.0 blank |
| Style Designator: |
| Rectangular terminal/terminals on one surface |
| |

N/a

NSN 5915-01-076-0402

Band Pass Filter - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A047b0