NSN 5915-01-076-0403

Band Pass Filter - Page 1 of 2



Overall Height:
1.110 inches
Body Length:
3.000 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 1.495 inches and 1.505 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.370 inches and 0.380 inches
Reference Frequency Per Function:
11.5 megahertz blank
Input Impedance Per Function W/load:
50.0 ohms blank
Output Impedance Per Function W/source Across Input:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.8 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity.
2 threaded stud
2 threaded stud
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity:
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function:
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function: 10.80 megahertz blank and 11.00 megahertz blank and 12.00 megahertz blank and 12.20 megahertz blank
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function: 10.80 megahertz blank and 11.00 megahertz blank and 12.00 megahertz blank and 12.20 megahertz blank Thread Size:
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function: 10.80 megahertz blank and 11.00 megahertz blank and 12.00 megahertz blank and 12.20 megahertz blank Thread Size: 0.112 inches
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function: 10.80 megahertz blank and 11.00 megahertz blank and 12.00 megahertz blank and 12.20 megahertz blank Thread Size: 0.112 inches Frequency Band Width Per Function:
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function: 10.80 megahertz blank and 11.00 megahertz blank and 12.00 megahertz blank and 12.20 megahertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 11.00 megahertz blank and 12.00 megahertz blank
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function: 10.80 megahertz blank and 11.00 megahertz blank and 12.00 megahertz blank and 12.20 megahertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 11.00 megahertz blank and 12.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:
2 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.25 blank Functional Terminal Type And Quantity: 2 pin ground 1st function Specified Frequencies Of Discrimination Per Function: 10.80 megahertz blank and 11.00 megahertz blank and 12.00 megahertz blank and 12.20 megahertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 11.00 megahertz blank and 12.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 6.0 blank and 1.5 blank and 6.0 blank

N/a

NSN 5915-01-076-0403

Band Pass Filter - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A047b0