

View Online at <https://aerobasegroup.com/nsn/5915-01-076-9941>

Body Length:

Between 5.480 inches and 5.520 inches

Body Width:

Between 4.750 inches and 4.790 inches

Body Height:

Between 0.860 inches and 0.900 inches

Unthreaded Mounting Hole Diameter:

Between 0.182 inches and 0.192 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 5.195 inches and 5.205 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 4.465 inches and 4.475 inches

Reference Frequency Per Function:

130.0 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

3.1 blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

2 connector, receptacle input-output/ground

Specified Frequencies Of Discrimination Per Function:

520.00 megahertz blank and 820.00 megahertz blank and 1.90 gigahertz blank

Frequency Band Width Per Function:

520.00 megahertz blank and 820.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

130.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0