

View Online at <https://aerobasegroup.com/nsn/5915-01-077-9096>

**Overall Length:**

1.750 inches

**Overall Height:**

0.400 inches

**Body Length:**

1.300 inches

**Body Width:**

0.400 inches

**Unthreaded Mounting Hole Diameter:**

0.070 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.180 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.280 inches

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

60.0 megahertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

1.4 blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.6 blank

**Functional Terminal Type And Quantity:**

1 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

54.00 megahertz blank and 57.00 megahertz blank and 63.00 megahertz blank and 66.00 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

57.00 megahertz blank and 63.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

29.0 blank and 3.0 blank and 3.0 blank and 21.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

57.0 megahertz blank and 63.0 megahertz blank

**Unpackaged Unit Weight:**

1.000 ounces

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0