

View Online at <https://aerobasegroup.com/nsn/5915-01-079-3243>

**Body Length:**

2.400 inches

**Body Width:**

1.062 inches

**Body Height:**

1.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.338 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Reference Frequency Per Function:**

21.4 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Average Power Rating Per Function:**

20.0 watts blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

5.00 megahertz blank and 17.40 megahertz blank and 25.40 megahertz blank and 120.00 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

17.40 megahertz blank and 25.40 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

30.0 blank and 3.0 blank and 3.0 blank and 30.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

17.4 megahertz blank and 25.4 megahertz blank

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0