Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-079-7404

| Overall Length |
|--|
| Overall Length: 2.720 inches |
| |
| Body Length: 2.000 inches |
| |
| Unthreaded Mounting Hole Diameter: |
| 0.160 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.500 inches |
| |
| Vibration Resistance Range In Hertz: +10.0/+2000.0 |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.240 inches |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Average Life Rating In Hours: |
| 10000.0 |
| End Application: |
| B-52 and c-135 aircraft |
| Source Impedance Rating Per Function: |
| 50.0 ohms 2nd radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 2nd radio interference |
| Power Line Frequency Rating Per Function In Hertz: |
| 425.0 1st radio interference |
| Operating Current Rating Per Function In Amps: |
| 1.4 1st radio interference |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance-resistance 1st radio interference |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Functional Terminal Type And Quantity: |
| 1 tab, solder lug output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 180.0 volts ac 2nd radio interference 2nd function |
| Body Material: |
| Metal |
| Body Surface Treatment: |
| Tin |
| Style Designator: |
| Rectangular terminal/terminals on opposite surfaces |

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0