## NSN 5915-01-079-9604

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-079-9604 **Body Length:** 8.344 inches **Body Width:** 2.812 inches **Body Height:** 5.438 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 7.344** inches Vibration Resistance Range In Hertz: +10.0/+55.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 4.438 inches **Operating Tempurature Range:** +0.0/+50.0 degrees celsius **Reference Frequency Per Function:** 70.0 megahertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Voltage Standing Wave Ratio Per Function:** 1.5 blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 3.5 blank **Functional Terminal Type And Quantity:** 1 connector, receptacle output 2nd function **Specified Frequencies Of Discrimination Per Function:** 1.00 megahertz blank and 69.60 megahertz blank and 70.40 megahertz blank and 140.80 megahertz blank **Thread Size:** 0.112 inches **Body Material:** Metal

**Frequency Band Width Per Function:** 

69.60 megahertz blank and 70.40 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:** 

48.0 blank and 3.0 blank and 48.0 blank

## NSN 5915-01-079-9604

Band Pass Filter - Page 2 of 2



	Voltage St	tanding Wav	e Ratio Freq	uency Limits	Per Function:
--	------------	-------------	--------------	--------------	---------------

69.6 megahertz blank and 70.4 megahertz blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0