

View Online at https://aerobasegroup.com/nsn/5915-01-080-6337

| Overall Length | |
|---------------------------------|--|
| Overall Length: 1.133 inches | |
| Body Length: | |
| | |
| 0.553 inches | |
| Body Outside Diam | eter: |
| 0.416 inches | |
| Vibration Resistanc | e Range in Hertz: |
| +10.0/+2000.0 | |
| Operating Tempura | - |
| -55.0/+125.0 degrees | |
| Average Life Rating | In Hours: |
| 1000.0 | |
| - | Rating Per Function: |
| 50.0 ohms blank | |
| Load Impedance Pe | r Function: |
| 50.0 ohms blank | |
| Operating Current F | Rating Per Function In Amps: |
| 1.0 blank | |
| Maximum Voltage D | Prop Per Function: |
| 0.25 volts dc blank | |
| Maximum Tempurat | ure Rise: |
| 25.0 degrees celsius | |
| Mounting Facility Se | crew Thread Series Designator: |
| Unf | |
| Inclosure Type: | |
| Hermetically sealed | |
| Mounting Facility Ty | /pe And Quantity: |
| 1 threaded bushing | |
| Functional Termina | Type And Quantity: |
| 1 tab, solder lug out | put 2nd function |
| Operating Voltage F | Rating And Type Per Function: |
| 100.0 volts dc blank | |
| Thread Size: | |
| 0.250 inches | |
| Body Material: | |
| Metal | |
| Style Designator: | |
| | nals on opposite surfaces |
| Test Data Documen | |
| | ecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| | nmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| | erformance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| environnentai anu pe | α α β |

Specification Data:

81349-mil-f-15733/25 government specification



Shelf Life:

N/a

Unit Of Measure:

--Demilitarization:

Yes - demil/mli

Fiig:

A047b0