

View Online at https://aerobasegroup.com/nsn/5915-01-081-5088

Overall Length:6.420 inchesBody Length:4.000 inchesBody Outside Diameter:1.750 inchesOperating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:30.0 blankMaximum Tempurature Rise:20.0 degrees celsiusMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:
Body Length:4.000 inchesBody Outside Diameter:1.750 inchesOperating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:30.0 blankMaximum Tempurature Rise:20.0 degrees celsiusMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:
4.000 inches Body Outside Diameter: 1.750 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Body Outside Diameter: 1.750 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
1.750 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
-55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Power Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:30.0 blankMaximum Tempurature Rise:20.0 degrees celsiusMounting Facility Screw Thread Series Designator:UnefInclosure Type:EncasedMounting Facility Type And Quantity:
400.0 blank Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Operating Current Rating Per Function In Amps: 30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
30.0 blank Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Maximum Tempurature Rise: 20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
20.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Mounting Facility Screw Thread Series Designator: Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Unef Inclosure Type: Encased Mounting Facility Type And Quantity:
Inclosure Type: Encased Mounting Facility Type And Quantity:
Encased Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 threaded stud output 2nd function
Operating Voltage Rating And Type Per Function:
120.0 volts ac blank and 400.0 volts dc blank
Thread Size:
0.750 inches
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
800.0 volts at sea level
Style Designator:
Round terminal/terminals on opposite surfaces
Shelf Life:
Shelf Life:
Shelf Life: N/a

No

NSN 5915-01-081-5088

Radio Frequency Interference Filter - Page 2 of 2

Fiig: A047b0

