

View Online at <https://aerobasegroup.com/nsn/5915-01-083-4838>

Overall Length:

4.125 inches

Body Outside Diameter:

1.125 inches

Vibration Resistance Range In Hertz:

+2.0/+2000.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Reference Frequency Per Function:

501.0 kilohertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Input Terminal Manufacturer Code:

21377

Input Terminal Identification:

Osm

Output Terminal Manufacturer Code:

21377

Output Terminal Identification:

Osm

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

5.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

3.00 kilohertz blank and 1.00 megahertz blank and 5.00 megahertz blank and 10.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

3.00 kilohertz blank and 1.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 60.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

3.0 kilohertz blank and 1.0 megahertz blank

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0