

View Online at <https://aerobasegroup.com/nsn/5915-01-084-2548>

Overall Height:

2.910 inches

Body Length:

1.720 inches

Body Width:

1.220 inches

Body Height:

2.530 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Reference Frequency Per Function:

2.0 kilohertz blank

Source Impedance Rating Per Function:

500.0 ohms blank

Load Impedance Per Function:

500.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 4.00 kilohertz blank and 6.00 kilohertz blank and 15.00 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 4.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

6.0 blank and 6.0 blank and 35.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-18327/65 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0