

View Online at <https://aerobasegroup.com/nsn/5915-01-084-8293>

**Overall Length:**

4.000 inches

**Overall Height:**

3.000 inches

**Body Length:**

3.000 inches

**Body Width:**

1.500 inches

**Body Height:**

3.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.600 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.100 inches

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Source Impedance Rating Per Function:**

50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

5.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

100.0 millivolts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Capacitance-inductance 2nd radio interference

**Maximum Temperature Rise:**

35.0 degrees celsius

**Average Power Rating Per Function:**

1.6 watts 2nd radio interference

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 captive screws

**Functional Terminal Type And Quantity:**

2 threaded stud output 3rd function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 2nd radio interference 2nd function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Special Features:**

Warning plate supplied with unit

**Unpackaged Unit Weight:**

1.500 pounds

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0