

View Online at <https://aerobasegroup.com/nsn/5915-01-085-0048>

Overall Length:

1.200 inches

Body Length:

0.750 inches

Body Width:

0.400 inches

Body Height:

0.400 inches

Unthreaded Mounting Hole Diameter:

0.070 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.630 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.280 inches

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Reference Frequency Per Function:

60.0 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.6 blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.75 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

54.00 megahertz blank and 57.00 megahertz blank and 63.00 megahertz blank and 66.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

57.00 megahertz blank and 63.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

12.0 blank and 3.0 blank and 3.0 blank and 12.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

57.0 megahertz blank and 63.0 megahertz blank

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

1.000 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0