

View Online at https://aerobasegroup.com/nsn/5915-01-086-1784

| Overall Length: |
|--|
| 3.891 inches |
| Body Length: |
| 2.750 inches |
| Body Width: |
| 2.000 inches |
| Body Height: |
| 2.000 inches |
| Source Impedance Rating Per Function: |
| 50.0 ohms 2nd radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 2nd radio interference |
| Power Line Frequency Rating Per Function In Hertz: |
| 60.0 2nd radio interference |
| Operating Current Rating Per Function In Amps: |
| 7.5 2nd radio interference |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| |
| 4 terminal |
| |
| 4 terminal |
| 4 terminal Functional Terminal Type And Quantity: |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on opposite surfaces |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: |
| 4 terminal Functional Terminal Type And Quantity: 3 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 120.0 volts ac 2nd radio interference 2nd function Body Material: Metal Style Designator: Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: No |