

View Online at <https://aerobasegroup.com/nsn/5915-01-087-2012>

Overall Height:

0.853 inches

Body Length:

2.730 inches

Body Width:

0.500 inches

Body Height:

0.619 inches

Unthreaded Mounting Hole Diameter:

0.030 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.200 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.200 inches

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Reference Frequency Per Function:

450.0 kilohertz blank

Source Impedance Rating Per Function:

20.0 kilohms blank

Load Impedance Per Function:

20.0 kilohms blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 threaded stud output 2nd function

Specified Frequencies Of Discrimination Per Function:

400.00 kilohertz blank and 442.00 kilohertz blank and 458.00 kilohertz blank and 500.00 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

442.00 kilohertz blank and 458.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank and 40.0 blank and 3.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0