NSN 5915-01-087-2012

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-087-2012

Overall Height:						
0.853 inches						
Body Length:						
2.730 inches						
Body Width:						
0.500 inches						
Body Height:						
0.619 inches						
Unthreaded Mounting Hole Diameter:						
0.030 inches						
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:						
2.200 inches						
Vibration Resistance Range In Hertz:						
+10.0/+500.0						
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:						
0.200 inches						
Operating Tempurature Range:						
-54.0/+85.0 degrees celsius						
Reference Frequency Per Function:						
450.0 kilohertz blank						
Source Impedance Rating Per Function:						
20.0 kilohms blank						
Load Impedance Per Function:						
20.0 kilohms blank						
Inclosure Type:						
Hermetically sealed						
Mounting Facility Type And Quantity:						
4 unthreaded hole						
Insertion Loss At Reference Frequency Per Function In Decibels:						
3.0 blank						
Functional Terminal Type And Quantity:						
1 threaded stud output 2nd function						
Specified Frequencies Of Discrimination Per Function:						
400.00 kilohertz blank and 442.00 kilohertz blank and 458.00 kilohertz blank and 500.00 kilohertz blank						
Body Material:						
Metal						
Frequency Band Width Per Function:						
442.00 kilohertz blank and 458.00 kilohertz blank						
Discrimination At Specificationified Frequencies Per Function In Decibels:						
3.0 blank and 40.0 blank and 40.0 blank and 3.0 blank						

Style Designator:

Rectangular terminal/terminals on one surface

NSN 5915-01-087-2012

Band Pass Filter - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0