NSN 5915-01-088-5207

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-088-5207

Overall Length:

3.080 inches

Body Outside Diameter:

0.250 inches

Vibration Resistance Range In Hertz:

+5.0/+33.0

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

4.096 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

2.0 watts blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

0.73 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.024 gigahertz blank and 3.434 gigahertz blank and 4.758 gigahertz blank and 7.168 gigahertz blank

Body Material:

Aluminum

Frequency Band Width Per Function:

3.434 gigahertz blank and 4.758 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

70.0 blank and 3.0 blank and 3.0 blank and 70.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

3.434 gigahertz blank and 4.758 gigahertz blank

Unpackaged Unit Weight:

0.770 ounces

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

NSN 5915-01-088-5207

Band Pass Filter - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0