

View Online at https://aerobasegroup.com/nsn/5915-01-088-8649

Overall Length: 4.370 inches Overall Height: 3.180 inches Body Length: 3.620 inches Body Width: 4.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Operating Current Rating Per Function In Amps: 5.5.4 th radio interference Mounting Facility Screw Thread Series Designator: Unc Incourse Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Thread Size: 0.138 inches Body Materiai: Metail Special Features: 9 functions Style Designator:	
Overall Height: 3.180 inches Body Length: 3.620 inches Body Width: 4.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Power Line Frequency Rating Per Function In Amps: 55.4 th radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 th treade hole Functional Terminal Type And Quantity: 4 threaded stud output 2nd function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions	Overall Length:
3.180 inches Body Length: 3.620 inches Body Width: 4.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Power Line Frequency Rating Per Function In Amps: 5.5.4 th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Encased Mounting Facility Type And Quantity: 15.0 volts a c fith radio interference 6th function Thread Size: 0.138 inches Bacy Material: Youting Facility Type And Quantity: 15.0 volts a c fith radio interference 6th function <td></td>	
Body Length: 3.620 inches Body Width: 4.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Power Line Frequency Rating Per Function In Amps: 55.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts a c6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: <t< td=""><td>Overall Height:</td></t<>	Overall Height:
3.620 inches Body Width: 4.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Power Line Frequency Rating Per Function In Ments: 55.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts a c 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator:	
Body Width: 4.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference Power Line Frequency Rating Per Function In Hertz: 4000 6th radio interference Operating Current Rating Per Function In Amps: 5.5 d+ tradio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Special Features: 9 functions	Body Length:
4.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Operating Current Rating Per Function In Amps: 5.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Incourse Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 1 threaded stud output 2nd function Chread Size: 0.138 inches Body Material: Metal Special Features: 9 functions	3.620 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:3.250 inchesOperating Tempurature Range:-55.0/+100.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 4th radio interferenceLoad Impedance Per Function:50.0 ohms 5th radio interferencePower Line Frequency Rating Per Function In Hertz:400.0 6th radio interferencePorating Current Rating Per Function In Amps:5.5 4th radio interferenceMaximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:NatalSecial Features:9 functionsSinchesBody Material:Notes ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:9 functionsSpecial Features:9 functionsSyle Designator:9 functionsSyle Designator:9 functionsSyle Designator:9 functionsSyle Designator:9 functionsSyle Designator:9 functions9 functions9 functions9 functions9 functions9 functions9 functions </td <td>-</td>	-
3.250 inches Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Operating Current Rating Per Function In Amps: 5.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: 9 functions	4.000 inches
Operating Tempurature Range: -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Operating Current Rating Per Function In Amps: 55.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Restangular terminal/terminals on adjacent surfaces	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
 -55.0/+100.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 4th radio interference Load Impedance Per Function: 50.0 ohms 5th radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 6th radio interference Operating Current Rating Per Function In Amps: 5.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces 	3.250 inches
Source Impedance Rating Per Function:50.0 ohms 4th radio interferenceLoad Impedance Per Function:50.0 ohms 5th radio interferencePower Line Frequency Rating Per Function In Hertz:400.0 6th radio interferenceOperating Current Rating Per Function In Amps:5.5 4th radio interferenceMaximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:9 functionsSpecial Features:9 functionsStyle Designator:9 functionsStyle Designator:9 functions	Operating Tempurature Range:
50.0 ohms 4th radio interferenceLoad Impedance Per Function:50.0 ohms 5th radio interferencePower Line Frequency Rating Per Function In Hertz:400.0 6th radio interferenceOperating Current Rating Per Function In Amps:5.5 4th radio interferenceMaximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	-55.0/+100.0 degrees celsius
Load Impedance Per Function:50.0 ohms 5th radio interferencePower Line Frequency Rating Per Function In Hertz:400.0 6th radio interferenceOperating Current Rating Per Function In Amps:5.5 4th radio interferenceMaximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionFureades!Body Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Source Impedance Rating Per Function:
50.0 ohms 5th radio interferencePower Line Frequency Rating Per Function In Hertz:400.0 6th radio interferenceOperating Current Rating Per Function In Amps:5.5 4th radio interferenceMaximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:9 functionsSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	50.0 ohms 4th radio interference
Power Line Frequency Rating Per Function In Hertz:400.0 6th radio interferenceOperating Current Rating Per Function In Amps:5.5 4th radio interferenceMaximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Load Impedance Per Function:
400.0 6th radio interference Operating Current Rating Per Function In Amps: 5.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	50.0 ohms 5th radio interference
Operating Current Rating Per Function In Amps:5.5 4th radio interferenceMaximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Power Line Frequency Rating Per Function In Hertz:
 5.5 4th radio interference Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces 	400.0 6th radio interference
Maximum Tempurature Rise:25.0 degrees celsiusMounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Operating Current Rating Per Function In Amps:
25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	5.5 4th radio interference
Mounting Facility Screw Thread Series Designator:UncInclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Maximum Tempurature Rise:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	25.0 degrees celsius
Inclosure Type:EncasedMounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Mounting Facility Screw Thread Series Designator:
Encased Mounting Facility Type And Quantity: 4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	Unc
Mounting Facility Type And Quantity:4 threaded holeFunctional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Inclosure Type:
4 threaded hole Functional Terminal Type And Quantity: 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	Encased
Functional Terminal Type And Quantity:9 threaded stud output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Mounting Facility Type And Quantity:
 9 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces 	4 threaded hole
Operating Voltage Rating And Type Per Function:115.0 volts ac 6th radio interference 6th functionThread Size:0.138 inchesBody Material:MetalSpecial Features:9 functionsStyle Designator:Rectangular terminal/terminals on adjacent surfaces	Functional Terminal Type And Quantity:
115.0 volts ac 6th radio interference 6th function Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	9 threaded stud output 2nd function
Thread Size: 0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	Operating Voltage Rating And Type Per Function:
0.138 inches Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	115.0 volts ac 6th radio interference 6th function
Body Material: Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	Thread Size:
Metal Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	0.138 inches
Special Features: 9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	Body Material:
9 functions Style Designator: Rectangular terminal/terminals on adjacent surfaces	Metal
Style Designator: Rectangular terminal/terminals on adjacent surfaces	Special Features:
Rectangular terminal/terminals on adjacent surfaces	9 functions
	Style Designator:
Shelf Life:	Rectangular terminal/terminals on adjacent surfaces
	Shelf Life:
N/a	N/a

Radio Frequency Interference Filter - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0