

View Online at <https://aerobasegroup.com/nsn/5915-01-090-1594>

**Body Length:**

2.520 inches

**Body Width:**

0.550 inches

**Body Height:**

0.550 inches

**Unthreaded Mounting Hole Diameter:**

0.093 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.127 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.340 inches

**Operating Temperature Range:**

-54.0/+110.0 degrees celsius

**Reference Frequency Per Function:**

2.0 gigahertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Input Terminal Manufacturer Code:**

24022

**Input Terminal Identification:**

Sma-jack

**Output Terminal Manufacturer Code:**

24022

**Output Terminal Identification:**

Sma-jack

**Voltage Standing Wave Ratio Per Function:**

1.3 blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.6 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 gigahertz blank and 4.15 gigahertz blank and 6.00 gigahertz blank and 12.00 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 gigahertz blank and 4.15 gigahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 1.0 blank and 40.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 gigahertz blank and 4.15 gigahertz blank

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0