

View Online at <https://aerobasegroup.com/nsn/5915-01-090-1594>

Body Length:

2.520 inches

Body Width:

0.550 inches

Body Height:

0.550 inches

Unthreaded Mounting Hole Diameter:

0.093 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.127 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.340 inches

Operating Temperature Range:

-54.0/+110.0 degrees celsius

Reference Frequency Per Function:

2.0 gigahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Input Terminal Manufacturer Code:

24022

Input Terminal Identification:

Sma-jack

Output Terminal Manufacturer Code:

24022

Output Terminal Identification:

Sma-jack

Voltage Standing Wave Ratio Per Function:

1.3 blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

0.6 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 gigahertz blank and 4.15 gigahertz blank and 6.00 gigahertz blank and 12.00 gigahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 gigahertz blank and 4.15 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 40.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 gigahertz blank and 4.15 gigahertz blank

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0