

View Online at <https://aerobasegroup.com/nsn/5915-01-090-3189>

Overall Height:

0.884 inches

Body Length:

2.730 inches

Body Width:

0.500 inches

Body Height:

0.619 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.500 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-20.0/+65.0 degrees celsius

Reference Frequency Per Function:

498.1 kilohertz blank

Source Impedance Rating Per Function:

2.0 kilohms blank

Load Impedance Per Function:

2.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

495.70 kilohertz blank and 497.94 kilohertz blank and 498.26 kilohertz blank and 500.30 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

497.94 kilohertz blank and 498.26 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Maximum Dielectric Withstanding Dc Voltage:

100.0 volts at sea level

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0