

View Online at <https://aerobasegroup.com/nsn/5915-01-090-5406>

Body Length:

Between 2.980 inches and 3.020 inches

Body Width:

Between 0.580 inches and 0.620 inches

Body Height:

Between 0.730 inches and 0.770 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.810 inches and 2.814 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.560 inches and 0.564 inches

Reference Frequency Per Function:

500.0 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

1.3 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 slot

Insertion Loss At Reference Frequency Per Function In Decibels:

0.4 blank

Functional Terminal Type And Quantity:

2 connector, receptacle input-output/ground

Specified Frequencies Of Discrimination Per Function:

65.00 megahertz blank and 85.00 megahertz blank and 16.00 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

65.00 megahertz blank and 85.00 megahertz blank

Discrimination At Specification Frequencies Per Function In Decibels:

19.0 blank and 20.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

500.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

80063-sm-a-935853 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0