

View Online at <https://aerobasegroup.com/nsn/5915-01-092-7780>

**Overall Length:**

Between 0.560 inches and 0.580 inches

**Overall Height:**

Between 1.041 inches and 1.091 inches

**Body Length:**

Between 0.350 inches and 0.430 inches

**Body Width:**

Between 2.800 inches and 2.820 inches

**Body Height:**

Between 0.743 inches and 0.753 inches

**Vibration Resistance Range In Hertz:**

+5.0/+200.0

**End Application:**

5895-01-056-0867 electronic comp

**Reference Frequency Per Function:**

630.0 megahertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Output Terminal Manufacturer Code:**

80063

**Output Terminal Identification:**

Sma-female receptacle

**Voltage Standing Wave Ratio Per Function:**

1.75 blank

**Average Power Rating Per Function:**

0.1 watts blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

5.5 blank

**Specified Frequencies Of Discrimination Per Function:**

540.00 megahertz blank and 622.50 megahertz blank and 637.50 megahertz blank and 720.00 megahertz blank

**Thread Size:**

0.086 inches

**Frequency Band Width Per Function:**

622.50 megahertz blank and 637.50 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

80.0 blank and 3.0 blank and 3.0 blank and 80.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

622.5 megahertz blank and 637.5 megahertz blank

**Unpackaged Unit Weight:**

2.500 ounces

**Style Designator:**

Rectangular terminal/terminals on two surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0