

View Online at https://aerobasegroup.com/nsn/5915-01-096-5897

Overall Length:
4.561 inches
Body Length:
3.500 inches
Body Outside Diameter:
1.125 inches
Vibration Resistance Range In Hertz:
+5.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
0.3 blank
Maximum Voltage Drop Per Function:
1.0 volts ac blank and 1.0 volts dc blank
Mounting Escility Serow Thread Series Designatory
Mounting Facility Screw Thread Series Designator:
Unf
Unf
Unf Inclosure Type:
Unf Inclosure Type: Hermetically sealed
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.438 inches
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.438 inches Body Material:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.438 inches Body Material: Metal
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.438 inches Body Material: Metal Unpackaged Unit Weight:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.438 inches Body Material: Metal Unpackaged Unit Weight: 6.500 ounces
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.438 inches Body Material: Metal Unpackaged Unit Weight: 6.500 ounces Style Designator:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 300.0 volts ac blank and 600.0 volts dc blank Thread Size: 0.438 inches Body Material: Metal Unpackaged Unit Weight: 6.500 ounces Style Designator: Round terminal/terminals on opposite surfaces



Demilitarization:

Yes - demil/mli

Fiig:

A047b0