NSN 5915-01-101-6137

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-101-6137

Overall Length:
Between 3.650 inches and 3.750 inches
Body Outside Diameter:
0.500 inches
Vibration Resistance Range In Hertz:
+5.0/+33.0
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Reference Frequency Per Function:
275.0 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.5 blank
Average Power Rating Per Function:
18.0 watts blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 terminal
Insertion Loss At Reference Frequency Per Function In Decibels:
0.75 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank
1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank
1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function:
 1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank
 1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:
 1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank
1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function:
 1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function: 1.0 hertz blank and 550.0 megahertz blank
1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function: 1.0 hertz blank and 550.0 megahertz blank Style Designator:
1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function: 1.0 hertz blank and 550.0 megahertz blank Style Designator: Round terminal/terminals on opposite surfaces
1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function: 1.0 hertz blank and 550.0 megahertz blank Style Designator: Round terminal/terminals on opposite surfaces Shelf Life:
1.00 hertz blank and 550.00 megahertz blank and 1.00 gigahertz blank and 2.00 gigahertz blank Frequency Band Width Per Function: 1.00 hertz blank and 550.00 megahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function: 1.0 hertz blank and 550.0 megahertz blank Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a

No

NSN 5915-01-101-6137

Low Pass Filter - Page 2 of 2



Fiig:

A047b0