

View Online at https://aerobasegroup.com/nsn/5915-01-103-0570

Overall Height: 2.740 inches Body Length: 3.070 inches Body Width: 2.070 inches Body Height: 1.570 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity: 4 threaded hole
Body Length: 3.070 inches Body Width: 2.070 inches Body Height: 1.570 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
3.070 inches Body Width: 2.070 inches Body Height: 1.570 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Body Width: 2.070 inches Body Height: 1.570 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
2.070 inches Body Height: 1.570 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Hertz: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Body Height: 1.570 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
1.570 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
1.500 inches Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Power Line Frequency Rating Per Function In Hertz: 400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
400.0 2nd radio interference Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Operating Current Rating Per Function In Amps: 2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
2.0 1st radio interference Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Unc Inclosure Type: Encased Mounting Facility Type And Quantity:
Inclosure Type: Encased Mounting Facility Type And Quantity:
Encased Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
4 threaded hole
Functional Terminal Type And Quantity:
2 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
125.0 volts ac 1st radio interference 1st function
Thread Size:
0.164 inches
Body Material:
Metal
Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Unit Of measure:

Yes - demil/mli

NSN 5915-01-103-0570

Radio Frequency Interference Filter - Page 2 of 2

Fiig: A047b0

