NSN 5915-01-103-7999

Radio Frequency Interference Filter - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5915-01-103-7999



Overall Height:
1.125 inches
Body Length:
2.000 inches
Body Width:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.562 inches
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
3.0 blank
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 unthreaded hole
2 unthreaded note
Functional Terminal Type And Quantity:
Functional Terminal Type And Quantity:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator: Rectangular terminal/terminals on one surface
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator: Rectangular terminal/terminals on one surface Shelf Life:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization:
Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 240.0 volts dc blank Body Material: Plastic Style Designator: Rectangular terminal/terminals on one surface Shelf Life: N/a Unit Of Measure: Demilitarization: No