NSN 5915-01-105-1960

High Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-105-1960
Overall Length:
1.760 inches
Body Length:
1.000 inches
Body Width:
0.880 inches
Body Height:
1.000 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Reference Frequency Per Function:
2.4 gigahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Input Terminal Manufacturer Code:
12436
Input Terminal Identification:
Sma-female
Output Terminal Manufacturer Code:
12436
Output Terminal Identification:
Sma-female
Voltage Standing Wave Ratio Per Function:
2.1 blank
Average Power Rating Per Function:
10.0 watts blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
1.5 blank

Functional Terminal Type And Quantity:

1 connector, plug output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 megahertz blank and 500.00 megahertz blank and 2.50 gigahertz blank and 18.50 gigahertz blank

NSN 5915-01-105-1960 High Pass Filter - Page 2 of 2



Thread Size:
0.086 inches
Body Material:
Metal
Frequency Band Width Per Function:
2.50 gigahertz blank and 18.50 gigahertz blank
Discrimination At Specificationified Frequencies Per Function In Decibels:
65.0 blank and 65.0 blank and 3.0 blank and 3.0 blank
Voltage Standing Wave Ratio Frequency Limits Per Function:
2.5 gigahertz blank and 18.5 gigahertz blank
Body Surface Treatment:
Cadmium
Unpackaged Unit Weight:
6.000 ounces
Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A047b0