

View Online at <https://aerobasegroup.com/nsn/5915-01-107-0907>

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Reference Frequency Per Function:

350.5 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

49956

Input Terminal Identification:

Mil-c-39012

Output Terminal Manufacturer Code:

49956

Output Terminal Identification:

Mil-c-39012

Voltage Standing Wave Ratio Per Function:

1.5 blank

Average Power Rating Per Function:

5.0 watts blank

Inclosure Type:

Encased

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

332.00 megahertz blank and 338.70 megahertz blank and 362.50 megahertz blank and 368.70 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

338.70 megahertz blank and 362.50 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 28.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

338.7 megahertz blank and 362.5 megahertz blank

Unpackaged Unit Weight:

1.000 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0

Mil-std (military Standard):

Mil-c-39012 spec.