

View Online at <https://aerobasegroup.com/nsn/5915-01-107-0908>

**Overall Length:**

1.660 inches

**Overall Height:**

0.500 inches

**Body Length:**

0.910 inches

**Body Width:**

1.690 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.663 inches

**Vibration Resistance Range In Hertz:**

+128.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.435 inches

**Operating Temperature Range:**

-54.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

1.0 kilohertz blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.6 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

250.00 hertz blank and 900.00 hertz blank and 1.10 kilohertz blank and 1.25 kilohertz blank

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

900.00 hertz blank and 1.10 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

20.0 blank and 12.0 blank and 12.0 blank and 20.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

900.0 hertz blank and 1.1 kilohertz blank

**Precious Material And Location:**

Connector body and hardware gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0