

View Online at <https://aerobasegroup.com/nsn/5915-01-107-0908>

Overall Length:

1.660 inches

Overall Height:

0.500 inches

Body Length:

0.910 inches

Body Width:

1.690 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.663 inches

Vibration Resistance Range In Hertz:

+128.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.435 inches

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Reference Frequency Per Function:

1.0 kilohertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.6 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

250.00 hertz blank and 900.00 hertz blank and 1.10 kilohertz blank and 1.25 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

900.00 hertz blank and 1.10 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

20.0 blank and 12.0 blank and 12.0 blank and 20.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

900.0 hertz blank and 1.1 kilohertz blank

Precious Material And Location:

Connector body and hardware gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0