

View Online at <https://aerobasegroup.com/nsn/5915-01-107-7158>

**Overall Height:**

Between 1.190 inches and 1.410 inches

**Body Length:**

Between 1.190 inches and 1.210 inches

**Body Width:**

Between 0.690 inches and 0.710 inches

**Body Height:**

Between 0.990 inches and 1.010 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.890 inches and 0.910 inches

**Vibration Resistance Range In Hertz:**

+5.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.490 inches and 0.510 inches

**Operating Temperature Range:**

-5.0/+75.0 degrees celsius

**Reference Frequency Per Function:**

200.0 kilohertz blank

**Source Impedance Rating Per Function:**

165.0 ohms blank

**Load Impedance Per Function:**

165.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 400.00 kilohertz blank and 800.00 kilohertz blank and 1.60 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 400.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 3.0 blank and 92.0 blank and 90.0 blank

**Body Surface Treatment:**

Tin

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0