

View Online at <https://aerobasegroup.com/nsn/5915-01-107-7158>

Overall Height:

Between 1.190 inches and 1.410 inches

Body Length:

Between 1.190 inches and 1.210 inches

Body Width:

Between 0.690 inches and 0.710 inches

Body Height:

Between 0.990 inches and 1.010 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.890 inches and 0.910 inches

Vibration Resistance Range In Hertz:

+5.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.490 inches and 0.510 inches

Operating Temperature Range:

-5.0/+75.0 degrees celsius

Reference Frequency Per Function:

200.0 kilohertz blank

Source Impedance Rating Per Function:

165.0 ohms blank

Load Impedance Per Function:

165.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 400.00 kilohertz blank and 800.00 kilohertz blank and 1.60 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.00 hertz blank and 400.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 92.0 blank and 90.0 blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0