NSN 5915-01-107-8596

Band Suppression Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-107-8596

Overall Length:
10.800 inches
Body Length:
10.000 inches
Body Width:
1.190 inches
Body Height:
4.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
9.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
-20.0/+50.0 degrees celsius
Reference Frequency Per Function:
29.0 kilohertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Hermetically sealed
Hermetically sealed Mounting Facility Type And Quantity:
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels:
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity:
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function:
 Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank
 Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank
 Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank Thread Size: 0.164 inches
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank Thread Size: 0.164 inches Body Material:
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank Thread Size: 0.164 inches Body Material: Metal
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank Thread Size: 0.164 inches Body Material: Metal Frequency Band Width Per Function:
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank Thread Size: 0.164 inches Body Material: Metal Frequency Band Width Per Function: 28.60 kilohertz blank and 29.40 kilohertz blank Metal Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 blank and 30.0 blank
Hermetically sealed Mounting Facility Type And Quantity: 8 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 0.25 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 28.20 kilohertz blank and 28.60 kilohertz blank and 29.40 kilohertz blank and 29.80 kilohertz blank Thread Size: 0.164 inches Body Material: Metal Frequency Band Width Per Function: 28.60 kilohertz blank and 29.40 kilohertz blank

NSN 5915-01-107-8596

Band Suppression Filter - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0

