NSN 5915-01-118-0384

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-118-0384

| Overall Length: |
|--|
| 1.374 inches |
| Body Length: |
| 0.500 inches |
| Vibration Resistance Range In Hertz: |
| +10.0/+2000.0 |
| Operating Tempurature Range: |
| -65.0/+85.0 degrees celsius |
| Average Life Rating In Hours: |
| 1000.0 |
| Source Impedance Rating Per Function: |
| 50.0 ohms blank |
| Load Impedance Per Function: |
| 50.0 ohms blank |
| Power Line Frequency Rating Per Function In Hertz: |
| 400.0 blank |
| Operating Current Rating Per Function In Amps: |
| 25.0 blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Maximum Tempurature Rise: |
| 15.0 degrees celsius |
| Mounting Facility Screw Thread Series Designator: |
| Unef |
| Inclosure Type: |
| Encased |
| Width Across Flats: |
| 0.390 inches |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Functional Terminal Type And Quantity: |
| 1 wire hook output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 350.0 volts ac blank and 500.0 volts dc blank |
| Thread Size: |
| 0.312 inches |
| Body Material: |
| Metal |
| Style Designator: |
| Round terminal/terminals on opposite surfaces |
| Test Data Document: |
| 81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5915-01-118-0384

Radio Frequency Interference Filter - Page 2 of 2



| | Sı | peci | fica | tion | Data |
|--|----|------|------|------|------|
|--|----|------|------|------|------|

81349-mil-f-15733/61 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0