

View Online at <https://aerobasegroup.com/nsn/5915-01-119-5126>

Body Length:

4.016 inches

Body Width:

3.172 inches

Body Height:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.400 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.565 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Reference Frequency Per Function:

80.0 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

79.84 kilohertz blank and 79.96 kilohertz blank and 80.04 kilohertz blank and 80.16 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

79.96 kilohertz blank and 80.04 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0