

View Online at <https://aerobasegroup.com/nsn/5915-01-121-9443>

Overall Length:

9.250 inches

Body Length:

8.500 inches

Body Width:

1.250 inches

Body Height:

1.700 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.000 inches

Operating Temperature Range:

+0.0/+57.0 degrees celsius

Reference Frequency Per Function:

2.0018 megahertz blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Input Terminal Manufacturer Code:

14632

Input Terminal Identification:

Sma

Output Terminal Manufacturer Code:

14632

Output Terminal Identification:

Sma

Voltage Standing Wave Ratio Per Function:

1.1 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

13.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.80 megahertz blank and 2.0002 megahertz blank and 2.0034 megahertz blank and 2.20 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

2.0002 megahertz blank and 2.0034 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

50.0 blank and 1.2 blank and 1.2 blank and 50.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

2.0002 megahertz blank and 2.0034 megahertz blank

Body Surface Treatment:

Tin

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0