

View Online at https://aerobasegroup.com/nsn/5915-01-123-9518

Overall Length:

- 6.188 inches
- **Overall Height:**
- 2.188 inches

Overall Width:

- 3.750 inches
- **Body Length:**
- 5.375 inches

Body Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.186 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.031 inches

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference3.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.25 volts ac 1st radio interference1.25 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Tempurature Rise:

25.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 unthreaded hole

Features Provided:

Magnetic case

Functional Terminal Type And Quantity:

2 turret input 1st function2 turret output 2nd function

Operating Voltage Rating And Type Per Function:

125.0 volts ac 1st radio interference 1st function125.0 volts ac 2nd radio interference 2nd function

NSN 5915-01-123-9518

Radio Frequency Interference Filter - Page 2 of 2



Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

250.0 volts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0