NSN 5915-01-124-9347

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-124-9347

Overall Length:
6.688 inches
Overall Height:
1.000 inches
Body Length:
6.000 inches
Body Width:
1.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
5.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Reference Frequency Per Function:
1.1 megahertz blank
Input Impedance Per Function W/load:
93.0 ohms blank
Output Impedance Per Function W/source Across Input:
93.0 ohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 threaded stud
4 threaded stud
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels:
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity:
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function:
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 megahertz blank and 1.30 megahertz blank and 1.35 megahertz blank and 100.00 megahertz blank
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 megahertz blank and 1.30 megahertz blank and 1.35 megahertz blank and 100.00 megahertz blank Thread Size:
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 megahertz blank and 1.30 megahertz blank and 1.35 megahertz blank and 100.00 megahertz blank Thread Size: 0.112 inches
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 megahertz blank and 1.30 megahertz blank and 1.35 megahertz blank and 100.00 megahertz blank Thread Size: 0.112 inches Body Material:
4 threaded stud Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 megahertz blank and 1.30 megahertz blank and 1.35 megahertz blank and 100.00 megahertz blank Thread Size: 0.112 inches Body Material: Metal
Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 megahertz blank and 1.30 megahertz blank and 1.35 megahertz blank and 100.00 megahertz blank Thread Size: 0.112 inches Body Material: Metal Frequency Band Width Per Function:

Style Designator:

Rectangular terminal/terminals on opposite surfaces

NSN 5915-01-124-9347

Low Pass Filter - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0