

View Online at <https://aerobasegroup.com/nsn/5915-01-125-5840>

Overall Length:

1.452 inches

Overall Height:

1.781 inches

Mounting Slot Width:

0.135 inches

Body Length:

0.975 inches

Body Width:

0.710 inches

Body Height:

1.157 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 5th radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 6th radio interference

Operating Current Rating Per Function In Amps:

10.0 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 6th radio interference

Distance Between Mounting Surface And Lower End:

0.938 inches

Maximum Temperature Rise:

15.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

6 slot

Functional Terminal Type And Quantity:

12 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

250.0 volts ac 6th radio interference 6th function

Body Material:

Metal

Special Features:

12 functions; item 1.202 in. W o/a

Unpackaged Unit Weight:

49.500 grams

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/63 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0