

View Online at <https://aerobasegroup.com/nsn/5915-01-135-5415>

Overall Length:

4.870 inches

Body Length:

3.750 inches

Body Width:

2.000 inches

Body Height:

2.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.250 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.250 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

2.0 1st radio interference 2.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.0 volts ac 1st radio interference 1.0 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Input Terminal Manufacturer Code:

28687

Input Terminal Identification:

Sma-connector

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.00 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

10.0 and 50.0 and 70.0 and 70.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

1 connector, plug input 1st function2 tab, solder lug output 2nd function2 tab, solder lug ground 3rd function

Operating Voltage Rating And Type Per Function:

130.0 volts ac 1st radio interference 1st function130.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.164 inches

Maximum Dielectric Withstanding Dc Voltage:

260.0 volts at sea level

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0