

View Online at <https://aerobasegroup.com/nsn/5915-01-135-7334>

**Overall Length:**

8.440 inches

**Mounting Slot Width:**

0.281 inches

**Body Length:**

Between 3.187 inches and 3.313 inches

**Body Width:**

Between 2.032 inches and 2.094 inches

**Body Height:**

Between 3.187 inches and 3.249 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.484 inches and 2.516 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.234 inches and 1.266 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

10.0 blank

**Maximum Voltage Drop Per Function:**

1.15 volts ac blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Full Load Insertion Loss Frequencies In Megahertz:**

0.01 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

40.0 and 80.0 and 80.0 and 80.0 and 80.0 and 80.0

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 slot4 threaded stud

**Features Provided:**

Mounting bracket and nut

**Functional Terminal Type And Quantity:**

1 threaded stud input 1st function1 threaded stud output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

230.0 volts at sea level

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac blank

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0