

View Online at <https://aerobasegroup.com/nsn/5915-01-135-8164>

Overall Length:

12.440 inches

Mounting Slot Width:

0.281 inches

Body Length:

Between 3.187 inches and 3.313 inches

Body Width:

Between 2.032 inches and 2.094 inches

Body Height:

Between 3.187 inches and 3.249 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.484 inches and 2.516 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.234 inches and 1.266 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

20.0 blank

Maximum Voltage Drop Per Function:

1.15 volts ac blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Full Load Insertion Loss Frequencies In Megahertz:

0.01 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

40.0 and 80.0 and 80.0 and 80.0 and 80.0 and 80.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 slot4 threaded stud

Features Provided:

Mounting bracket and nut

Functional Terminal Type And Quantity:

1 threaded stud input 1st function1 threaded stud output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

230.0 volts at sea level

Operating Voltage Rating And Type Per Function:

115.0 volts ac blank

Thread Size:

0.190 inches

Body Material:

Metal

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0